

VW Temperature Sensor VWTS-6000

The Geosense® VWTS 6000 vibrating wire temperature sensor is used primarily for the measurement of internal temperature in concrete structures, soil, rock or water



VW Temperature Sensor VWTS-6000



Overview



The Geosense® VWTS 6000 vibrating wire temperature sensor is used primarily for the measurement of internal temperature in concrete structures, soil, rock or water.

The sensor operates on the principle that when plucked, a tensioned wire vibrates at its resonant frequency. The square of this frequency is proportional to the strain in the wire.

Around the wire is a magnetic coil which when pulsed by a vibrating wire readout or data logger interface plucks the wire and measures the resultant resonant frequency of vibration.

The sensor consists of a tensioned wire clamped inside a stainless steel cylinder. Changes in temperature cause the stainless steel body to expand and contract at a different rate to that of the vibrating wire thus altering the resonant frequency.

The thermal response of the VWTS 6000 is relatively slow and is therefore not suitable for measuring rapidly changing temperatures.

The VWTS 6000 vibrating wire temperature sensor is fitted with an internal gas-discharge tube for lightning protection.

APPLICATIONS

Monitoring temperatures in or on:

Dams

Concrete structures

Geothermal wells

Soil & rock temperatures

Water temperature

FEATURES

Accurate

High resolution

Long-term stability

Insensitive to long cable lengths.

Accuracy

Integral Thermistor

Integral lightning protection

Suitable for remote reading and data logging



VW Temperature Sensor VWTS-6000

Specifications

GENERAL

Operating temperature range	-20°C to +80°C*
Non linearity	<0.5% FS
Operating frequency	2000 to 3500 Hz
Cable	4 x 22 AWG (shielded)
Cable Type	Type 900 - VW Sensor with Foil Screen & Drain Wire
Weight	210 g
Dimension	20mm diameter x 140mm long
*Other ranges available on request	

ORDERING INFORMATION

Cable length
Terminal box - number of terminals
Special mounting brackets

READOUT

The VWTS-6000 vibrating wire temperature sensor may be read by the VW-2106 or any vibrating wire readout device and may be readily data logged using Campbell Scientific or any other data loggers with vibrating wire interface modules.

Vibrating wire temperature sensors output a frequency signal and are therefore insensitive to resistance changes in connecting cables caused by contact resistance or leakage to ground.

Cable may be readily and simply extended on site without special precautions. Gauges may be read up to 3000 metres away from their installed location without change in calibration.



Geosense Ltd, Nova House, Rougham Industrial Estate, Rougham, Bury St Edmunds, Suffolk IP30 9ND, England

www.geosense.co.uk e sales@geosense.co.uk t +44(0)1359 270457

Specifications are subject to change without notice and should not be construed as a commitment by Geosense. Geosense assumes no responsibility for any errors that may appear in this document. In no event shall Geosense be liable for incidental or consequential damages arising from the use of this document or the systems described in this document. All Content published or distributed by Geosense is made available for the purposes of general information. You are not permitted to publish our content or make any commercial use of our content without our express written consent. This material or any portion of this material may not be reproduced, duplicated, copied, sold, resold, edited, or modified without our express written consent.

V1.7 06/2023